



The BIOVERSAL trolley type fire extinguisher range with ecological additive meets all your needs when it comes to the environment and using them in the long-term. Ideal in providing the user with optimal security, the range combines protection of the environment, performance and aesthetics. To be used on class A fires (wood, paper, etc.), class B (petrol, fuel oil, etc.) and class F (cooking oil, etc.). Designed in compliance with regulatory requirements and with an eco-design approach, it responds to the requirements of industrial, service industry, food-processing and domestic activities.

MANUFACTURING :

- Green label printing for immediate identification of the fire extinguishing agent,
- Anti-corrosion and anti-UV treatment thanks to polyester paint,
- Reinforced semi-rigid pipe. Spring avoiding deformation and crushing.

MANOEUVRABILITY - COMFORT :

- Hand truck designed according to the standards of handling trolleys,
- Wheel axle (590-600mm) designed to run between doors, according to NF P20 - 101 standard,
- Inclined hand truck for easy tipping and handling,
- Ergonomically designed Blower for easy handling and increased precision,
- Holding of the hose by the side hooks,
- Standard long length hose (5m) for more freedom of movement.

MAINTENANCE :

- Pressure gauge to check if the unit is operational,
- Fast and safe maintenance,
- Checking of the pressure gauge secured by the valve piston.

PERFORMANCES :

- Valve immediately accessible for quick intervention,
- Among the top-performing products on the market in its category.

ENVIRONMENT:

- Non-corrosive and non-toxic additive for a better protection of the user and the working environment,
- 100% vegetable-based, non-synthetic additive,
- Go beyond the requirements of the REACH regulations,
- Interruption of bacterial growth.
- Additive certified free of PFOS and PFOA with their persistent and bioaccumulative fluorinated derivatives.
- Highly biodegradable » additive according to OECD test no. 301.

Eurofeu controls the life cycle of the product, from manufacturing to denaturation.



PRODUCT HIGHLIGHTS

- Recognised innovation and exclusivity by its numerous awards and honours,
- Optimal protection of people, goods and the environment.



Site de production
Senonches (28)

Conception, fabrication, vente, négoce de
composants et de matériels de lutte contre
l'incendie, maintenance d'extincteurs et
formation incendie

SPARE PARTS

- 1 Rear wheel Ø 300
- 2 Wheel stopper
- 3 Valve
- 4 Manometer
- 5 Blower Cap green
- 6 Spray Nozzle
- 7 Discharge hose with blower
- 8 Seal
- 9 Holding clips
- 10 Safety Pin
- 11 Deep tube
- 12 Head seal
- 13 Hand truck
- 14 Nut M10x1.5
- 15 Sticker

50 L
A001747
A024652
A019475
A001055
A021866
A024024
A019394
A001726
A025629
A001195
A019396
A026492
A026368
A001266
A026368



TECHNICAL FEATURES

50 L BIOVERSAL	
Nominal Charge	50 L
Extinguishing Agent	47 L Water + 3 L BIOVERSAL®
Fire Rating	A-B-F
Weight in Working Order	83 kg
Height	1091 mm
Overall Width	558 mm
Diameter	350 mm
Propelling Agent	Nitrogen + 3% Helium at 12 bar
Operating temperature	0°C +60°C
Discharge time	3 min 20 sec
Attack distance	3 to 2 m
Stop valve	5m Hose + Blower gun
Palettisation	700 mm x 680 mm

FORMULA
ΠΥΡΟΣΒΕΣΤΗΡΕΣ



VOTRE CONTACT

FORMULA Πυροσβεστήρες ΑΕ

Καπανέως 73, Αθήνα - Τηλ. 210 5157400
formula.com.gr / info@formula.com.gr