

SIMPO

Addressable Fire Alarm Panel

Description

Simpo is the perfect cost effective solution for smaller addressable installations. It is an up to two loop panel with coverage of 16 zones. 250 devices with Teletek Electronics protocol could be connected to each loop. System status is visualized via LCD display and LED indication. The panel comes in a metal casing with a multilanguage display and front foil for easier customization.

Direct programming with *ProsTE* software.



Functional Specifications

Loops	Up to 2
Devices per loop	250
Zones	16
Outputs (monitored, relay)	5
Outputs (monitored, programmable, relay)	4, 230/10A
Inputs	3
Memory LOG.	10 000
Display	4*40 symbols
Multilanguage support	Yes
Day/Night Mode	Yes

Technical Specifications

Main Power Supply	90 ÷ 264 VAC
Frequency	47 ÷ 440 Hz
Back-up Power Supply	1 battery, 12V/ 18Ah
Electrical output	4,7A
Operating temperature.	-10°C to +50°C
Relative humidity resistance	95 %
Weight (without battery)	~4,2kg
Dimensions	308x415x78mm

Compatible Products

- Simpo TTE Loop
- SensolRIS Detectors
- SensolRIS Modules
- SensolRIS Sounders/Strobes
- Observer Monitoring Software
- ProsTE Programming Software

Contact Information: